

libNEGF: a portable library for quantum transport

Alessandro Pecchia, CNR-ISMN

Daniele Soccodato, Matthias Auf der Maur, University of 'Tor Vergata'
Christoph Conrads, Edoardo Di Napoli, Forschungszentrum Jülich



EERA-CASTIEL2 Webinar




EuroHPC
Joint Undertaking



Co-funded by
the European Union



*lib*NEGF as a general purpose library



- Interface any **local** Hamiltonian (FEM, ETB, DFTB, Wannier, Wavelets, LCAO-DFT)
- Basis-set agnostic
- Beyond coherent transport (**el-phonon**, **el-photon**, ...)
- Ported to Nvidia GPU (CUDA)


Fortran2003/2008/CUDA

<http://www.github.com/libnegf>

Tight Development Collaboration



A. Buttari



B. Aradi







L. Genovese, W. Dawson








What's for ?

Gate All-around SiNW *nano* MOSFETs





Address nanoscale transport / PV devices

Transport in MoS₂ with S-vacancies



What's for ?


Multi QW solar cells based on InGaN/GaN



Density of states and J-V characteristics of the 30 QW active region

<https://github.com/tiberlab>

NEGF equations + External Self-consistent loop



Implemented Self-energies

- Elastic deformation potential scattering

$$\Sigma_{\mu\mu}^<(k, E) = \frac{1}{A} \sum_{\alpha, \lambda, q} \frac{\hbar^2 \Omega_{cell}}{2\hbar \omega_{q\lambda} m_\alpha} \Xi_\lambda^2 q^2 (2N_q + 1) G_{\mu\mu}^<(k - q, E) \approx \frac{k_B T \Xi_{LA}^2}{\rho c_{LA}^2} \langle G_{\mu\mu}^<(k, E) \rangle_{BZ} \approx \frac{k_B T \Xi_{LA}^2}{\rho c_{LA}^2} G_{\mu\mu}^<(k, E)$$

- Inelastic non-polar Optical within deformation potential

$$\Sigma_{\mu\mu}^<(k, E) = \frac{\hbar^2 \Xi_o^2}{2\hbar \omega_o \rho} \left[(N_q + 1) G_{\mu\mu}^<(k, E - \hbar \omega_o) + N_q G_{\mu\mu}^<(k, E + \hbar \omega_o) \right]$$

- Inelastic polar Optical Frölich coupling


$$\Sigma_{\mu\nu}^<(k, E) = \sum_q F(|z_\mu - z_\nu|, k, q) \left[(N_o + 1) G_{\mu\nu}^<(q, E - \hbar \omega_o) + N_o G_{\mu\nu}^<(q, E + \hbar \omega_o) \right]$$

- Electron-photon self-energy

$$\Sigma_{\mu\nu}^<(k, E) = M_{\mu\sigma} \left[(N_\gamma + 1) G_{\sigma\tau}^<(k, E - \hbar \omega_\gamma) + N_\gamma G_{\sigma\tau}^<(k, E + \hbar \omega_\gamma) \right] M_{\tau\nu}$$

Parallelization strategy

2D MPI cartesian grid: Energies and k-points



Typical size of the grid


k-mesh: 8x8 grid = 64 points

E-grid: ~100 points

⇒ 6400 points


Spatial domain distribution under development

Ballistic runs (no scattering)



Strong scaling benchmarks


Block-Recursive algorithm for G^r and $G^<$




SiNW



3-diagonal block-dense representation




Communications needed for $\Sigma_{scatt}^{r,<}(k,E)$





- E, k grids are independent of spatial domain
- Parallelize on spatial domain $\Rightarrow$ 3D cartesian grid

Benchmarks – Strong Scaling



Layer size: 288x288
Number of Layers: 10




67%

- Benchmarks run on a small Si system with a 2x2 cell with 10 Layers
 - Full inelastic calculation including 1 PO phonon
 - Solution of the SCBA loop
 - Calculation of the layer-to-layer current

Block-recursive routines on GPUs

All recursive numerical algorithms implemented in libNEGF have been ported to GPU

We use a more flexible CUDA implementation interfacing cuBLAS/cuSolver kernels



Speedup of GPU vs CPU for a single MPI task
GPU vs multithreaded CPU: Nvidia A100 vs Intel Xeon 8168

Profiling of selected intensive parts in **single-precision**

Size	Mat Size	CPU (threaded)	GPU	Tens.-C	Speedup
4.8 nm	5832	119 s	1.4 s	0.42 s	x30 - x120
6.5 nm	10368	450 s	4.0 s	1.19 s*	x100 - x400
9.2 nm	20736	3600 s	30.0 s	8.2 s*	x120 - x440

Peak performance on tens.C exceeds 90 Tflops/s

Numerical issues to run the whole NEGF algorithms in sp.

⇒ Mixed precision solutions are needed

Summary

- libNEGF is an LGPL library for NEGF available on github
- Active development involving CNR, JSC, CNRS-IRIT
- API that can interface F2003, C++, Python
- Runs on Intel/NVIDIA arch. (Juwels Booster, LEONARDO, JEDI, etc.)
Work in progress: porting to LUMI (AMD).
- Codes currently interfaced:
 - dftb+ (semi-empirical DFT method, F2003)
 - tiberCAD (FEM, ETB methods, C++)
 - bigDFT (ab-initio wavelet method, work in progress)

THANK YOU